

1 TONNE 4x4 GS CARGO



ANA TON

TECHNICAL SPECIFICATIONS

ENGINE TYPE (2GD - FTV) 16	2393 cc, 4 Cylinder In-Line, V, DOHC Intercooler VNT Diesel
DIMENSION 5,70	00 mm x 1,850 mm x 2,400 mm
FUEL INJECTION TYPE	Common Rail Direct Injection
APPROACH ANGLE	30 Degree
DEPARTURE ANGLE	22 Degree
WHEELBASE	3,085 mm
OVERHANG FRONT	1,300 mm
REAR	1,300 mm
KERB WEIGHT	2,370 kg
GROSS VEHICLE WEIG	HT 3,380 kg
PAYLOAD	1,000 kg
GROUND CLEARANCE	220 mm
CLIMBING PERFORMAN	CE 50% Gradient, Hill Stop
SIDE SLOPE	30%

CHASIS		TOYOTA HILUX SINGLE CAB
MAX OUTPUT (Ps)		150 Ps (110 kW) / 3,400 rpm
MAX TORQUE (Nm)		400 Nm / 1,600 - 2,000 rpm
TRANSMISSION		6 - Speed Manual
SUSPENSION	FRONT	Independent Double Wishbone
		with Coil Spring & Stabilizer
	REAR	Leaf Spring, Rigid Axle
BRAKE	FRONT	Ventilated Disc
	REAR	Leading - Trailing Drum
DRIVETRAIN		Part-Time 4WD with Automatic
		Disconnecting Differential (ADD)
FUEL CAPACITY 80 L		
STEERING		Power Steering RHS
TYRE		AT 265/65/R17
		(Full Size Spare Tyre)