

LIGHT TACTICAL VEHICLE



TECHNICAL SPECIFICATIONS

ENGINE TYPE	4 Cylinders In-Line DOHC 16V MIVEC VG Turbo Intercooler	MAX PAYLOAD	1,000 kg
ENGINE SIZE (CC)	2,442	ANGLE OF APPROACH	35
FUEL TYPE	Diesel	ANGLE OF DEPARTURE	30
EMISSION STANDARD	Euro 4	FUEL TANK CAPACITY (L)	75
BORE STROKE (MM)	86.0 x 105.1	TRANSMISSION TYPE	6 Speed Automatic
MAX OUTPUT (KW) / HORSE POWER (PS)	133/181 at 3,500 rpm	BRAKE	Dual Circuit Hydraulic with Vacuum Servo Assisted
MAX TORQUE (NM)	430 at 2,500 rpm	LENGTH X WIDTH X HEIGHT	5,355 x 2,085 x 2,818
GROSS VEHICLE WEIGHT	3,350 kg - 4,450 kg	TYRES	Mud Terrain (M/T) 265/75 R16, INCL Space Tyre
GROUND CLEARANCE	200mm, LTV 230mm, Field Ambulance	WHEEL TYPE	Steel
FORDING DEPTH	600 mm		
KERB WEIGHT	2,350 kg - 3,450 kg		